

PRODUCT INTRODUCTION

eBox-WIFI-01-WIFI Serial Server



Dear user: Thanking you for selecting our product!

Product Introduction

eBox-WIFI-01 is a kind of serial server which can make our company's solar controller and inverter be with wifi communication function, and carry out wireless monitoring, parameter settings, and etc. for the system only by cooperating with mobile phone APP. Plug and play, simple and convenient set, it has many excellent features.

Main features:

- > Realize wireless monitoring function of solar controller and inverter
- > Support mobile phone APP, plug and play, simple and convenient to set
- Use high performance CPU with core M4
- Ultra-low power consumption and high speed data processing capability
- No need of external power supply
- Communication distance up to 50 m
- One-key restore the factory settings

Product Features



- ①RS485 Port (RJ45): Used for connecting the solar controller or inverter with **RS485** communication bus
- ②Reload Button: One-key restore the factory settings
- 3 Link indicator: Communication connection indicator
- (4) Power indicator: Power indicator

Indicator Instructions			
Indicator	status	Instruction	
Power indicator	Green on solid	Normal power-on	
	OFF	No power-on	

1

Link indicator	Green on solid	WIFI connected
	OFF	WIFI not connected

System Connection Diagram



NOTE: Standard network cable(Parallel cable) can achieve the connection!

Applicable Models

Tel: +86-10-82894112 / 82894962

Product series	Communication	Interface type
LS-B series		
VS-A series	RS485	
VS-BN series		
Tracer-A series		RJ45
Tracer-BN series		
SHI series		
STI series		
eTracer-AD series		
eTracer-BND series		3.81-4P
iTracer-ND series		

Operation Instruction

For details, please refer to the user manual of mobile phone APP [EPEVER (WIFI)] of this product!

Technical Specifications

Models		
Item	eBox-WIFI-01	
Input Voltage	5VDC	
	(Direct powered by RS485 port)	
Standby power	0.20W	
consumption		
Operation power	0.25W	
consumption		
Communication	≤50m	
distance		
Port baud rate	300bps~230400bps(Default 115200)	
Communication	RS485 to WIFI	
Interface type	RJ45	
Connecting cable	Standard network cable (Parallel cable)	
Overall dimension	51*67*24.5mm	
Mounting dimension	41.2	
Mounting hole size	Ф3.2	
Working temperature	-35~75℃	
Enclosure	IP30	
Net weight	39g	

Any changes without prior notice! Version number: V1.0