



## D-NS Series(Dual-MPPT, Single-Phase)

GoodWe D-NS series inverter adopts cutting-edge technology in photovoltaic fields, designed under modern industrial concept. Inheriting all the excellent traits from GoodWe SS and DS series, the D-NS series is much smarter in size and weight. Excellent cooling design, comprehensive software and hardware technology is guaranteed to maximize the life-span of these inverters.

- Up to 10 safety measurements
- DC switch
- IP65 dust-proof and water-proof
- 45°C full-load output
- Built-in anti-reverse function
- 30% lighter than similar products
- 20% Volume optimization
- Wide range of MPPT voltage
- Multiple monitoring and communication
- Fanless low-noise design

Technical Data	GW3000D-NS	GW3600D-NS	GW4200D-NS	GW5000D-NS
<b>DC Input Data</b>				
Max. recommended PV Power [W]	3900	4680	5460	6500
Nominal DC Power [W]	3300	3960	4600	5500
Max. DC voltage [V]	580	580	580	580
MPPT voltage range [V]	80~550	125~550	125~550	125~550
Starting voltage [V]	120	120	120	120
Max. DC current [A]	11/11	11/11	11/11	11/11
No. of DC connectors	2	2	2	2
No. of MPPTs	2 (can parallel)	2 (can parallel)	2 (can parallel)	2 (can parallel)
DC connector	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol
<b>AC Output Data</b>				
Normal AC power [W]	3000	3680	4200	5000*
Max. AC power [W]	3000	3680	4200	5000*
Max. AC current [A]	13.6	16	19	22.8
Normal AC output	50/60Hz; 230Vac		50/60Hz; 230Vac	
AC output range	45~55Hz/55~65Hz; 180~270Vac		45~55Hz/55~65Hz; 180~270Vac	
THDi	<1.5%		<1.5%	
Power factor	0.8 leading~0.8 lagging		0.8 leading~0.8 lagging	
Grid connection	Single phase		Single phase	
<b>Efficiency</b>				
Max. efficiency	97.8%	97.8%	97.8%	97.8%
Euro efficiency	>97.5%	>97.5%	>97.5%	>97.5%
MPPT adaptation efficiency	99.9%	99.9%	99.9%	99.9%
<b>Protection</b>				
Residual current monitoring unit	Integrated	Integrated	Integrated	Integrated
Anti-islanding protection	Integrated	Integrated	Integrated	Integrated
DC switch	Integrated (optional)	Integrated (optional)	Integrated (optional)	Integrated (optional)
AC over current protection	Integrated	Integrated	Integrated	Integrated
Insulation monitoring	Integrated	Integrated	Integrated	Integrated
<b>Certifications &amp; Standards</b>				
Grid regulation	VDE-AR-N 4105, EN50438, VDE0126-1-1, AS4777.2&.3, G83/G59	VDE-AR-N 4105, G83/G59, VDE0126-1-1, EN50438, AS4777.2&.3, MEA,PEA	VDE-AR-N 4105, EN50438, VDE0126-1-1, G83/G59	VDE-AR-N 4105, EN50438, VDE0126-1-1, G83/G59, AS4777.2&.3, MEA, PEA
Safety	IEC62109-1&-2, AS3100			
EMC	IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, IEC/EN 61000-6-4, IEC/EN 61000-3-11, IEC/EN 61000-3-12			
<b>General Data</b>				
Dimensions (WxHxD) [mm]	347*432*145	347*432*145	347*432*145	347*432*145
Weight [kg]	14	14	14	14
Mounting	Wall bracket	Wall bracket	Wall bracket	Wall bracket
Ambient temperature range	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)
Relative humidity	0~95%	0~95%	0~95%	0~95%
Max. operating altitude	4000m(> 3000m derating)	4000m(> 3000m derating)	4000m(> 3000m derating)	4000m(> 3000m derating)
Protection degree	IP65	IP65	IP65	IP65
Topology	Transformerless	Transformerless	Transformerless	Transformerless
Night power consumption [W]	<1	<1	<1	<1
Cooling	Natural convection	Natural convection	Natural convection	Natural convection
Noise emission [dB]	<25	<25	<25	<25
Display	LCD	LCD	LCD	LCD
Communication	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi
Standard warranty [years]	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)

\*Note: 4600W for VDE-AR-N4105