

Deutsche
Qualität
Garantiert



144

HALF
CELLS

182
mm

CELL
SIZE



LID
RESISTANT



PID
RESISTANT



SALT CORROSION
RESISTANT



SAND
RESISTANT



AMMONIA
RESISTANT



HIGHLY STABLE
AND TOUGH



mete  r

POWER MORE, DEGRADE LESS

30

years

Performance
Guarantee

15

years

Product
Warranty


N-TYPE TOPCON TECHNOLOGY PV MODULES
HALF-CUT CELLS • MONO-FACIAL

560W-580W
AE CMD-144 Series



IEC 61215
IEC 61730
Regular Production Surveillance
Type Tested and Monitored

IEC 62716 (Ammonia corrosion)
IEC 61701 (Salt mist corrosion)
IEC 60068 (Sand and dust)
IEC 62804 (PID resistance)




www.ae-solar.com

AE CMD-144 Series 560W-580W

Mechanical and design specification

Cell type	N-type TOPCon Technology, Half-cut cells, 182 mm
No. of cells	144
Glass	3.2 mm, high transmission, AR coated, tempered
Encapsulation	EVA
Back cover	White Backsheet
Junction box	IP68, 3 Bypass Diodes
Frame	30 mm anodized Aluminium alloy
Cable	1 × 4 mm ² , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2278 mm x 1133 mm x 30 mm
Weight	26.5 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa/ 244 kg/ m ²
Mechanical load	5400 Pa/ 550 kg/ m ²





Packaging information

Packaging configuration	72 pcs / double pallets
Loading capacity	720 pcs / 40 HQ
Size / Double pallets	2310 mm x 1140 mm x 2490 mm
Weight	1996 kg / double pallets

Temperature ratings

Operating temperature	(°C)	-40 to +85
Temp.coefficient of P _{max}	(%/°C)	-0.3
Temp.coefficient of V _{oc}	(%/°C)	-0.25
Temp.coefficient of I _{sc}	(%/°C)	0.045
Nom. operating temp. NOCT	(°C)	42 ± 2



Electrical specifications (STC*):	AE560CMD-144	AE565CMD-144	AE570CMD-144	AE575CMD-144	AE580CMD-144	
Nominal Max. Power	P _{max} (Wp)	560	565	570	575	580
Maximum operating voltage	V _{MPP} (V)	42.40	42.56	42.72	42.88	43.04
Maximum operating current	I _{MPP} (A)	13.21	13.28	13.34	13.41	13.49
Open-circuit voltage	V _{oc} (V)	50.23	50.39	50.55	50.68	50.86
Short-circuit current	I _{sc} (A)	14.14	14.20	14.26	14.33	14.40
Module efficiency	η (%)	21.70	21.89	22.08	22.28	22.47
Power tolerance	(W)			0~+5		
Maximum system Voltage	(V)			1500		
Maximum series fuse rating	(A)			25		

*STC: Standard test conditions (Irradiance 1000 W/m², Cell temperature 25°C and air mass of AM1.5)

Electrical specifications (NMOT*):	AE560CMD-144	AE565CMD-144	AE570CMD-144	AE575CMD-144	AE580CMD-144	
Nominal Max. Power	P _{max} (Wp)	426.0	430.1	434.0	437.4	440
Maximum operating voltage	V _{MPP} (V)	39.3	39.5	39.7	39.8	39.9
Maximum operating current	I _{MPP} (A)	10.84	10.89	10.94	10.99	11.04
Open-circuit voltage	V _{oc} (V)	47.5	47.7	47.8	48.0	48.2
Short-circuit current	I _{sc} (A)	11.40	11.45	11.50	11.55	11.60

*NMOT: Normal Module Operating Temperature (Irradiance 800 W/m², Ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.